

80mm Thermal Receipt Printer


TRP-9909

Features:

- Mini structure and light weight, easy to carry.
- Wireless Bluetooth connection (Wi-Fi optional).
- Supported Android and Windows systems.
- Supported to print 1D Barcode and QR Code.



80mm




Easy loading



Barcode



Bluetooth



Fast Speed



Windows



WIFI



Retail

Specifications

Printing Method	Direct Line Thermal
Interfaces	USB / LAN / Bluetooth /WIFI(optional)
Print Comand	ESC / POS command
Print Speed	220mm/s
Resolution	203DPI (8dot/mm)
TPH Reliability	100km
Auto Cutter	Full / Partial (Factory default)
Cutter Life	1.5 million cuts
Logo	Support downloading and printing logo
Line Spacing	3.75mm (Adjustable by commands)
Extension Character Sheet	PC437 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran, Windows-1252, PC866 (Cyrillic#2), PC852 (Latin2), Pc858, IranII, Latvian, Arabic, Thai, PT151 (Windows-1251).
Character Size	ANK, Font A: 1.5×3.0 mm (12×24 dots); Font B: 1.1×2.1 mm (9×17 dots) Simplified Chinese, Traditional Chinese: 3.0×3.0 mm (24×24 dots).
Supported Code	1D: UPC-A/UPC-E/JAN13(EAN13)/JAN8 (EAN8)/CODE39/ITF/CODABAR/CODE93 /CODE128. 2D: QR CODE, PDF417.
Input Buffer	80K bytes
NV Flash	320K bytes

Driver	Windows/Linux/Mac OS/OPOS/Android
Power Adapter	Input: AC 100-240V, 50-60Hz; Output: DC 24V/1.25A
Cash Drawer	DC 24V/1A

Paper

Paper Types	Thermal Roll Paper
Paper Width	79.5±0.5mm / ϕ 83 mm
Print Width	72mm
Paper Thickness	0.06-0.08 mm

Package

Printer Dimension	16*13.5*12.2 CM
Printer N.W.	0.72 kg
Package	1pc with accessories/Box, 12 boxes/CTN
Accessories	Manual, USB Cable, Power Adapter, Paper Roll
Box Dimension	20.3*18.6*13.9 CM
Box G.W.	1.1 Kgs
CTN Dimension	62.9*39.2*29.8 CM
CTN G.W.	14 Kgs

Environmental Requirements

Work Environment	Temperature (0-45℃); humidity(10-80%)
Storage Environment	Temperature(-10-60℃); humidity(10-90%)